



Vredo Dodewaard bv  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

vredo.com

ART.NUMBER

DETAILS

C001097

VREDO VT3936

VT3936

- Year of manufacturing 2007
- Mach. Nr. 0109.042
- 19m<sup>3</sup> tank
- Ca. 12.300 hours
- Trimble GPS
- Reload docking arm

VT 3936 self propelled trac is equipped with:

- Engine Deutz 286 kW / 390 pk watercooled COM II
- Transmission mechanical-hydraulic stepless 0 - 40 kph at 1.500 rpm Engine speed with automatic drive computer
- Fuel tank 500 liter
- Suspended SUPERComfort Vredo cab, incl. airco and radio with CD player
- Airsuspended Grammer Maximo supercomfort seat
- Passenger seat (foldable)
- Elektrical adjustable and heated mirrors and wide angle mirrors
- Mechanical differential lock at front- and rear axle
- Steering Frontwheel-, fourwheel- and Crabsteer
- Suspended front axle with automatic levelling and shock absorber
- 3-Point double operating linkage at rear, steered, torsion compensated and floating position. Lift capacity 7,8 ton. Active operated: pressurised, floating or lifted, operated from cab
- Remote control for tipping of slurry tank
- Automatic greasing
- 1 Closed system hydraulic pump, 150 l/min, 400 bar
- 2 LS-Pumps, 160 l/min, 200bar tbv. auxiliary functions, pressure compensated valves
- 3 Double operating valves
- Footswitch slurry pump
- Camera- monitor installation with LCD colour display and sound
- Rear drive alarm
- 2 beacon on cab roof

The tank is equipped with the following as standard:

- Complete construction 4 mm steel
- Light weight (2530kg)
- Tank volume 19 m<sup>3</sup>
- Tank is easy to clean due to the uniformity of its shape
- Tank is easy to remove
- Airing with vacuum protection
- Pump automatically switches off when full
- Tank can be hydraulically lifted for maintenance

Pump-filter unit PF9000:

- Vogelsang displacement pump VX186-390QD 9000 l/min with spiral plungers
- Reverse option on slurry pump operated by button in cabin
- Filling at reduced rpm (1,200)
- Cutting filter VREDO FT5100 with dirt ejector, opened and emptied from cabin
- Suction arm 8", can be swivelled 160°, together with 9000 l/min Vogelsang slurry pump and FT5100 cutting filter on separate removable front unit.
- 180° swivelling front-suction connection 6"
- Electric/hydraulic operating
- Dosing independent of driving speed and slurry distribution can be set (e.g. unloading when standing still)
- 3 different working widths pre-programmed

**Will be sold in customer order:**

Herr Hendrik Schulze  
+49 170 3120936

# Vredo

Vredo Dodewaard bv  
Welysestraat 25a  
6669 DJ Dodewaard (NL)  
Tel. +31(0)488411254  
info@vredo.com

Your fields,  
our passion

[vredo.com](http://vredo.com)

